



Westinghouse

INNOVATION YOU CAN BE SURE OF



R-410A
Roof Top
Package Unit
3 Tr - 20 Tr.

Technical Specifications: One way Air Outlet - Side

Model Number			WPCX-036KA4	WPCX-048KA4	WPCX-060KA4	WPCX-060CA4
Nominal Ton	Tr.		3	4	5	5
Power Supply	V - Ph - Hz		208~230V,1PH,60Hz	208~230V,1PH,60Hz	208~230V,1PH,60Hz	208~230V,3PH,60Hz
Cooling Capacity	Btu/h		36,000	48,000	60,000	60,000
Power Input	Kw.		4	5.1	5.9	6
Max. Input Consumption	Kw.		5	5	6.2	7.7
Max. Current	A		24	24	31	40
Performance	Air Flow	CFM	1200	1500	1700	1700
	ESP	Pa	40	50	50	50
Indoor Fan	Type		Centrifugal Blower	Centrifugal Blower	Centrifugal Blower	Centrifugal Blower
	Drive		Direct	Direct	Direct	Direct
Compressor	Type		Scroll	Scroll	Scroll	Scroll
	Qty.		1	1	1	1
Outdoor Fan	Type		Axile	Axile	Axile	Axile
	Drive		Direct	Direct	Direct	Direct
Refrigerant	Type		R410A	R410A	R410A	R410A
	Kg.		2	3.1	3.1	3.3
Filter	Qty.		1	1	1	1
Dimension (W x H x D)	Unit	mm	1116 x 830 x 744	1116 x 830 x 744	1116 x 830 x 744	1116 x 830 x 744
	Packing	mm	1152 x 855 x 765	1152 x 855 x 765	1152 x 855 x 765	1152 x 855 x 765
Weight	Net	Kg.	149	161	170	169
	Gross	Kg.	152	164	173	172

Technical Specifications: Two-way Air Outlet

Model Number			WPAXH-060CA4	WPAXH-090CA4	WPAXH-120CA4	WPAXH-180CA4	WPAXH-240CA4
Nominal Ton	Tr.		5	7.5	10	15	20
Power Supply	V - Ph - Hz		208~230V,3PH,60Hz	208~230V,3PH,60Hz	208~230V,3PH,60Hz	208~230V,3PH,60Hz	208~230V,3PH,60Hz
Cooling Capacity	Btu/h		60,000	90,000	120,000	180,000	240,000
Power Input	Kw.		5.6	9.2	11.4	18.1	23.6
Max. Input Consumption	Kw.		8.3	13.2	16.8	26.8	38.2
Max. Current	A		28.5	42	55	87.9	127.3
Performance	Air Flow	CFM	1970	3000	3800	6600	8400
	ESP	Pa	70	60	75	90	100
Indoor Fan	Type		FC Centrifugal	FC Centrifugal	FC Centrifugal	FC Centrifugal	FC Centrifugal
	Drive		Direct	Belt	Belt	Belt	Belt
Compressor	Type		Scroll	Scroll	Scroll	Scroll	Scroll
	Qty.		1	1	1	2	2
Outdoor Fan	Type		Axial Fan	Propeller	Propeller	Propeller	Propeller
	Drive		direct	Direct	Direct	Direct	Direct
Refrigerant	Type		R410A	R410A	R410A	R410A	R410A
	Kg.		3.6	5.6	6.5	5.8 X 2	7.2X 2
Filter	Qty.		1	2	2	2	2
Dimension (W x H x D)	Unit	mm	1920 x 840 x 1068	1630 x 1065 x 1068	2165 x 1021 x 1335	2230 x 1245 x 1824	2230 x 1245 x 1824
	Packing	mm	1955 x 870 x 1085	1700 x 1110 x 1160	2220 x 1140 x 1415	2236 xx1300 x 1855	2236 x 1300 x 1855
Weight	Net	Kg.	228	315	445	710	730
	Gross	Kg.	232	335	458	730	750

Specifications and illustrations subject to change without notice and without incurring obligations.

For More Information, call or visit your Westinghouse Dealer