

# HI WALL 60 Hz



Comfort and intelligence in air conditioning®



## Features:

**R-410A**  
REFRIGERANT

- Cooling Only
- R-410A refrigerant
- Remote control
- LED Display
- Sleep Mode
- Easy clean panel
- Quiet operation
- Auto restart function
- Dehumidification Mode
- Anti Mildew
- Auto Diagnostic function

### TECHNICAL SPECIFICATIONS

Outdoor Unit Model No.		CG41A-009-H3U2C	CG41A-012-H3U2C	CG41A-018-H3U2C	CG41A-024-H3U2C
Model number including piping kit		CG41A-009PH3U2C	CG41A-012PH3U2C	CG41A-018PH3U2C	CG41A-024PH3U2C
Power supply		208-230V/60Hz/1Ph			
Cooling capacity	BTUH	9,000	12,000	18,000	24,000
EER	BTUH/W;	10	9.9	9.1	9.0
Dimensions (W x H x D)	mm	600x500x232	700x552x256	760x552x256	902x650x307
Net Weight	kg	24	28	35	52
Packing dimensions (W x H x D)	mm	754x542x353	803x598x380	863x598x376	1037x705x433
Gross weight	kg	27	31	39	58
Voltage range	V	198~253	198~253	198~253	198~253
Current	A	4.4	5.8	9.1	13.2
Compressor		Rotary	Rotary	Rotary	Rotary
Noise level	dB(A)	52	55	58	60
Connecting Pipe (Gas)	Inches	3/8"	3/8"	1/2"	5/8"
Connecting Pipe (Liquid)	Inches	1/4"	1/4"	1/4"	3/8"
Indoor Unit Model No.		CH41A-009-H3U2C	CH41A-012-H3U2C	CH41A-018-H3U2C	CH41A-024-H3U2C
Dimensions (W x H x D)	mm	718x240x180	770x240x180	898x280x202	1033x313x202
Net weight	kg	7	8	11	14
Packing dimensions (W x H x D)	mm	805x305x255	855x305x255	995x365x298	1103x400x300
Gross weight	kg	9	10	14	17
Noise level	(Hi/Med/Lo)	36/34/32	39/36/34	48/46/44	48/46/43
Maximum pipe length	m	15	15	15	15
Maximum vertical separation	m	5	5	5	5



Carrier InterAmerica Corporation  
Miami, Florida USA  
[www.ciac-comfort.com](http://www.ciac-comfort.com)

Authorized Dealer: